Bohnenkamp

Moving Professionals



Pneu 200 / 70 R 16, Agrimax RT 765 94 A8 / 94 B, TL BKT

Product-No.: 15726540

Technical Information:

	15700510
Product number	15726540
Tyre Size	200 / 70 R 16
R / D	Radiálne
TL/TT	TL
LI / SI	94 A8 / 94 B
Profile	Agrimax RT 765
Manufacturer	ВКТ
Recom. Rim	W6
Permissible rim	7.0
Width mm	197
Outer diameter mm	686
Static radius mm	313
Rolling circumference mm	2037
Payload in kg at kph (1)	670 / 40
Payload in kg at kph (2)	670 / 50
Inflation pressure bar	2,40
Weight kg	16
Tyre content 75% litre	20.25
Stud height mm	26,0
Number of studs	18x2
Certified	ECE 106
Nominal width [mm]	200
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symetrické

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp s.r.o. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.