Bohnenkamp Moving Professionals

BKT



Pneu 280 / 70 R 16, Agrimax RT 765 112 A8 / 112 B, TL BKT

Product-No.: 15726560

Technical Information:

Product number	15726560
Tyre Size	280 / 70 R 16
R / D	Radiálne
TL/TT	TL
LI / SI	112 A8 / 112 B
Profile	Agrimax RT 765
Manufacturer	ВКТ
Recom. Rim	W9
Permissible rim	W8, W8L, W10
Width mm	282
Outer diameter mm	798
Static radius mm	356
Rolling circumference mm	2370
Payload in kg at kph (1)	1120 / 40
Payload in kg at kph (2)	1120 / 50
Inflation pressure bar	2,40
Weight kg	25,6
Tyre content 75% litre	45
Stud width mm	25
Stud height mm	32,0
Certified	ECE 106
Nominal width [mm]	280
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symetrické

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp s.r.o. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.