Bohnenkamp Moving Professionals



Pneu 215 / 70 R 15 C, MR-W300 8 PR, 109 / 107 R, TL, 3PMSF Mirage

Product-No.: 10165820

Technical Information:

Product number	10165820
Tyre Size	215 / 70 R 15 C
R / D	Radiálne
TL/TT	TL
LI / SI	109 / 107 R
PR	8
Profile	MR-W300
Manufacturer	Mirage
Specification	3PMSF
Recom. Rim	6.5J
Permissible rim	5.50J, 6J, 7J
Width mm	221
Outer diameter mm	683
Static radius mm	311
Rolling circumference mm	2069
Payload in kg at kph (1)	1030 / 170
Inflation pressure bar	4,50
Weight kg	12,60
Rolling resistance	D
Wet grip	D
Rolling noise DB	73
Rolling noise level	В
Stud height mm	9,7
Certified	ECE 117, ECE 54
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	215
Aspect ratio	70
Commercial van mark	С
Tread symmetry	symetrické

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp s.r.o. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.