Bohnenkamp Moving Professionals



Pneu VF 540 / 65 R 30, Agriflex 372 + 161 D, TL, Steel Belted Alliance

Product-No.: 10001570

Technical Information:

Product number	10001570
Tyre Size	VF 540 / 65 R 30
R / D	Radiálne
TL/TT	TL
LI / SI	161 D
Profile	Agriflex 372 +
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW20B
Permissible rim	W18L, DW18L
Width mm	549
Outer diameter mm	1464
Static radius mm	659.2
Rolling circumference mm	4346
Payload in kg at kph (1)	4625 / 65
Inflation pressure bar	2,40
Weight kg	152,00
Tyre content 75% litre	327.3
Stud height mm	48,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	540
Aspect ratio	65
Tyre technology	VF
Direction bound	Yes
Tread symmetry	symetrické

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp s.r.o. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.