Bohnenkamp Moving Professionals



Pneu VF 480 / 60 R 28, Agriflex 372 + 149 D, TL, Steel Belted Alliance

Product-No.: 10001571

Technical Information:

Product number	10001571
Tyre Size	VF 480 / 60 R 28
R / D	Radiálne
TL/TT	TL
LI/SI	149 D
Profile	Agriflex 372 +
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW16L
Permissible rim	W15L
Width mm	470
Outer diameter mm	1287
Static radius mm	573.1
Rolling circumference mm	3762
Payload in kg at kph (1)	3250 / 65
Inflation pressure bar	2,00
Weight kg	108,70
Tyre content 75% litre	202.05
Stud height mm	46,0
Number of studs	19x2
Certified	ECE 106
Nominal width [mm]	480
Aspect ratio	60
Tyre technology	VF
Direction bound	Yes
Tread symmetry	symetrické

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp s.r.o. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.